

Shinju [Shin jū]

Shinju, which means “pearl” in Japanese, translates the shimmer of pearls, the ridges of oyster shells, the surrounding reefs, and the movement of the ocean into a handcrafted ceramic tile series. The effect is one of modern elegance with coastal inspiration and a nod to nature’s artistry.



SCAN CODE FOR MORE INFORMATION ON THE SHINJU COLLECTION



Up To **45%** Post-Consumer Recycled Content

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2024 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	Yes ▲	Yes ▲
Fireplace/Cooktop Surround	Yes *	Steam Shower	Yes ▲	N/A
Shower Wall	Yes	Light Residential	Yes	No
Steam Shower	Yes **	Residential	No	No
Exterior Wall	Yes **	<i>DCOF Value of ≥0.42 is accepted value for use in commercial applications. A 137.1-2018</i>		
Pool, Spa or Water Feature (fully submerged)	Yes **			

PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage	Packaging (Per Box)	Standards Methods		
Cambric Hex (2")	0.795 SF/Sheet	5 Sheets/3.975 SF	Breaking Strength	ASTM C-648	> 450 PSI
Crest (4")	0.84 SF/Sheet	5 Sheets/4.20 SF	Water Absorption	ASTM C-373	Vitreous ≥ 0.5% -≤ 3.0%
Liner (¾ x 9 ½")	0.787 LF/PC	80 Pieces/63 LF	Chemical Resistance	ASTM C-650	Unaffected
Reef (2 ½ x 9 ½")	0.155 SF/PC	32 Pieces/4.96 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Silhouette Mosaic (1 ¼ x 1 ¼")	0.857 SF/Sheet	5 Sheets/4.285 SF	Warpage	ASTM C-485	± 0.26% /± 1.5mm
Smooth (2 ½ x 9 ½")	0.155 SF/PC	32 Pieces/4.96 SF	NOTES Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).		
Stingray (3 ½ x 6")	0.770 SF/Sheet	5 Sheets/3.85 SF			
Swell Mosaic (¾ x 3 ¾, 1 ¼ x 3 ¾")	0.92 SF/Sheet	5 Sheets/4.60 SF			
Surf Rail (2 ½ x 9 ½")	0.787 LF/PC	24 Pieces/18.9 LF			
Tide (4 x 4")	0.103 SF/PC	48 Pieces/4.928 SF			
Shade Variation	Grout Joint Recommendation		MAINTENANCE A routine cleaning of Shinju tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner. Products with low pH and low alkalinity used for cleaning can eventually dull the finishes of Cape Pearl, Olympia, and Pacific over time.		
V1 - V3 Moderate Variation	1/8" (3 mm)				

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. **NOT** recommended for placement inside a firebox.

** **Metallic Glazes:** Cape Pearl, Olympia and Pacific are not recommended for installations in pools, spas, water features, steam showers or exterior walls directly exposed to elements. All other colors are acceptable.

▲ Cambric Hex, Silhouette Mosaic, Stingray, Swell Mosaic and Tide in Kumamoto, Kushi and Moonstone **ONLY**, no other patterns or colors are acceptable.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.