## **Tozen**

Like the art of watercolor, the Tozen collection uses transparency, pigment and light to tell a story. Translucent glass presents our artists the perfect canvas to juxtapose luminosity and darkness...transparency and opacity...rest and movement. The handcrafted, smooth-edged design is available in 19 colors and two finishes to narrate your personal design story.





Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Applicat	ion	Suitable		Interior	Exterior
Interior Wall/Backsplash		Yes	Shower	Yes	Yes
Fireplace/Cooktop Surround		Yes *	Steam Shower	Yes A	N/A
Shower Wall		Yes	Light Residential	Yes	No
Steam Shower		Yes	Residential	No	No
Exterior Wall		Yes **	Note: Silk finish is recommended for floor/foot traffic applications and		
Pool, Spa or Water Feature (fully s	ubmerged)	Yes A	usage.		
PRODUCT SPECS		TESTING			
Size	Coverage	Packaging			

PRODUCT SPECS					
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet/Piece)	Packaging (Per Box)			
½ x ½ Mini Mosaic	1.09	5 Sheets/5.45 SF	Ві		
½ x 1 Mini Brick	1.09	5 Sheets/5.45 SF	W		
½ x 4 Brick	0.84	5 Sheets/4.20 SF	Cl		
1 x 1 Mosaic	1.09	5 Sheets/5.45 SF	Fi		
1 x 2 Brick	1.00	5 Sheets/5.00 SF	TI		
1 x 4 Brick	0.85	5 Sheets/4.25 SF			
1 x 4 Herringbone	0.69	5 Sheets/3.45 SF	Sin sel res		
2 x 6 Brick	5.046	58 Pieces/Box			
Japonaise (½ x 1", 1 x 1")	1.09	5 Sheets/5.45 SF			
Martini (5/8 x 2")	1.04	5 Sheets/5.20 SF	fro 109		
Moyou (½ x 4", 1 x 4")	0.68	5 Sheets/3.40 SF	the		
Pompeii (½ x ½")	1.08	5 Sheets/5.40 SF	Gr		
Rio (½ × 1", 1 × 1")	1.27	5 Sheets/6.35 SF	car <b>co</b> l		
Tresse (½ x 1", 1 x 4")	0.78	5 Sheets/3.90 SF	со		
Wings (1 x 1")	1.03	5 Sheets/5.15 SF			
Shade Variation	Grout Joint Recommendation				
V4 - Random Variation	1/16" (1.6 mm)		_		

1 X 4 Herringbone	0.03	3 311eets/ 3.43 31	
2 x 6 Brick	5.046	58 Pieces/Box	
Japonaise (½ x 1", 1 x 1")	1.09	5 Sheets/5.45 SF	
Martini (% × 2")	1.04	5 Sheets/5.20 SF	
Moyou (½ x 4", 1 x 4")	0.68	5 Sheets/3.40 SF	
Pompeii (½ x ½")	1.08	5 Sheets/5.40 SF	
Rio (½ x 1", 1 x 1")	1.27	5 Sheets/6.35 SF	
Tresse (½ x 1", 1 x 4")	0.78	5 Sheets/3.90 SF	
Wings (1 x 1")	1.03	5 Sheets/5.15 SF	
Shade Variation	Grout Joint Recommendation		
V4 - Random Variation	1/16" (1.6 mm)		

Standards Methods					
Breaking Strength	ASTM C-648	>350 PSI			
Water Absorption	ASTM C-373	Impervious < 0.05%			
Chemical Resistance	ASTM C-650	Unaffected			
Freeze/Thaw	ASTM C-1026	Unaffected			
Thermal Shock	ASTM C-484	Passed			

## **NOTES**

nce variations are common in artistic glass tile, we recommend final election be made from an actual tile mock-up. To achieve optimal sults in shading, layout and design, tile should be randomly selected om multiple boxes during installation. We recommend a minimum of 0% overage on all orders. On dimensional patterns, using a grout bag is ne best method to target competent and successful grout application. rout floats should not be used due to the luster glaze. please take are when grouting and protect surface from abrasion. Installation onstitutes acceptance. We advise retaining control samples to aid in olor matching if additional material is required (match not guaranteed).

## MAINTENANCE

A routine cleaning of Tozen tile can be done with a light duty nonabrasive, close to neutral pH detergent cleaner.

- \* Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.
- \*\* Size and Pattern Limitations: 2 x 6" is NOT recommended for exterior walls.
- ▲ Size and Pattern Limitations: 1/2 x 4", 1 x 4", 1 x 4" Herringbone, 2 x 6", Moyou, and Tresse, are NOT recommended for use or installation in a submerged application such as a pool/spa or steam shower floors.
- Size and Pattern Limitations: 2 x 6" is for interior wall and shower wall use only, and is NOT recommended for use or installation on floors.

## FLOOR APPLICATION DEFINITIONS:

**Light Residential** - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.